Item	Piece	Product	Unit price EURO	Total price EURO
		AEROLIFE		
		Wall-mounted ventilator with sound absorption and heat recovery		
		Individual room ventilation unit for the simultaneous ventilation and aerating of rooms with the following additional features:		
		Suitable for outer wall construction or for recessed installation in the outer wall.		
		Airflow by means of separated blower units via split pipe sockets and adapter for wall thicknesses up to 425 mm.		
		Weather grille		
		Sound insulation value: $D_{n,e,w} = 52 \text{ dB}$		
		Air throughput ventilation and exhaust: Level 1 approx. $29 \text{ m}^3/\text{h}$ at $L_{PA} = 26 \text{ dB}$ (A) Level 2 approx. $35 \text{ m}^3/\text{h}$ at $L_{PA} = 30 \text{ dB}$ (A) Level 3 approx. $60 \text{ m}^3/\text{h}$ at $L_{PA} = 40 \text{ dB}$ (A)		
		Inherent noise L _{PA} measured in accordance with DIN EN ISO 3745 (with room insulation 8 dB).		
		Power consumption: max. 32 Watt Electrical connection: 230 Volt ~ / 0.17 amps Protection class: II, insulated		
		A safety switch is also integrated for maintenance purposes.		
		If the front panel is removed, the safety switch cuts off the internal voltage supply.		
		With integrated heat exchanger for heat recovery in winter fresh air operation.		
		Heat recovery efficiency max. 66 %.		
		The unit can be controlled manually or automatically depending on the humidity.		
		With integrated three-layer synthetic composite filter, filter class F7. Optional NOx filter F7 (nitrogen dioxide, fine dust, pollen) available.		
		Technical approval (DIBt)		
		Product: SIEGENIA AEROLIFE		
		Supply of unit including accessories:		
		Unit installation:		S
		Electrical connection:		
				HAS WANTER MIDORGEN TO B 2016/2